



## High Track

High Pressure Non Compliant Rapid Exchange PTCA Balloon Catheter

**High Track** is designed for use in highly calcified lesions or for post dilation of stents. High Track provides advantage over the PET balloons with a balloon wall more resistant to puncture and burst, especially with highly calcified lesions. The unique hypotube facilitate easy transfer of torque and enhanced pushability.



Low profile balloon ideal for post-dilation.



Suited for tortuous lesions.

### Size sheet

<b>Diameters (Φ)</b>	2.50mm, 2.75mm, 3.00mm, 3.25mm, 3.50mm, 3.75mm and 4.00mm
<b>Length</b>	10mm, 12mm, 14mm, 15mm, 16mm, 18mm, 20mm, 23mm, 25mm & 30mm

*CE marked*

*Available in custom sizes, and on OEM and OBL basis.*

The ultra-high pressure, non compliant balloon material allows for controlled dilation post stent placement. The High Track balloon catheters are available in varying diameters, and lengths.

Custom sizes available on request.

Technical Specifications	
Balloon Material	NYLON
Balloon Material Type	Non Compliant
Proximal Shaft	1.9 Fr
Distal Shaft	2.6Fr
Balloon Folding	Tri Fold
Inflation/Deflation time	10seconds/25seconds
Guidewire diameter	0.014"
Catheter Length	142cm
Marked Bands	90cm and 100cm
Nominal Pressure	12 atm
Rated Burst Pressure	20 atm

### VASMED TECHNOLOGIES LTD FZC

Plot No. L314  
Fujairah Free Zone, Fujairah  
United Arab Emirates  
Ph: +971 9 222 88 62  
Fax: +971 9 222 88 63  
Email: sales@vasmed.ae  
www.vasmedtech.com

Document Number: VM-PS-BALLOON-01, Rev No. 04

www.vasmedtech.com